# **SMOK**<sup>®</sup>

**SMOK**<sup>®</sup>

AL85 Kit

### Introduction:

AL85 Kit, consists of AL85 mod and TFV8 Baby tank features with delicate design, smooth streamline and integrated functional buttons. You would enjoy thoughtful experience and innovative design from SMOK when its 85W output power combines with Cloud Beast TFV8 Baby tank. Vaping, just enjoy it. Innovation keeps changing the vaping experience!

# The Kit Includes

1 x AL85 Mod 1 x TFV8 Baby Tank (3ml) 1 x V8 Baby-Q2 Core (0.4Ω dual coils) (Pre-installed) 1 x V8 Baby-Q2 Core (0.6Ω dual coils) 1 x USB Charge/Upgrade Cable 1 x USB Charge/Upgrade Cable 1 x User Manual Spare Parts Spare Parts

# **Specifications**

AL85 Mod Size: 71x48x27mm Size: / 1x40x2/min Weight: 120g Power Range: 1-85W Voltage Range: 0.35V-8.0V Resistance Range: 0.10Ω-3.00Ω (VW Mode) / 0.06Ω-3.00Ω (TC Mode) Temperature Range: 200-600<sup>°</sup>F/100-315<sup>°</sup>C

TFV8 Baby Tank Material: Stainless Steel Size: 22mmx53mm Weight: 47g Capacity: 3ml Thread: 510

# 2

4

8

### Warranty

AL85 Kit Warranty Period: 6 Months from the Purchase Date. Within the 6 Months, some items may not be eligible for service due to misuse, damage, or other failures caused other than by manufacturer defects or  $premature\ failure.\ Please\ contact\ SMOK\ Authorized\ Vendor\ for\ more$ information and terms of service. The "AL85 Kit Customer Card" is an important proof for customers to get

warranty service, please keep it. And read the card carefully and fill it out correctly. Warranty requests must be accompanied by this card. For more warranty policy and process, please visit our official website: http://www.smoktech.com/support/

# **User Guide**

# Preparation before use:

VIPIease make sure the battery you used is according with the BATTERY WARNING CARD. 2)Before enjoy vaping, please make sure the tank is filled with enough e-juice.

Install Battery 1)Screw off the battery cover counterclockwise; 2)Place the battery into the device according to the correct directions; 3)Close the battery cover.



### Verification

1

3

1.Using your Smartphone or PC to visit SMOK official website: http://www.smoktech.com/support/ 2.Scratch off the coating of the security label on packing box to get the 16 anti-

fake codes. Fill them into the input box on the webpage to verify. The result will come out after a few seconds. 3.If you have any question, please contact SMOK consultant via e-mail, phone

or our website to get more help.

Welcome to download our APP:Vaping Tour, share your vaping experience and communicate with global vapor fans.



Components Drip Tip Тор Сар Glass Tube 🚽 Battery Cover Coil Head Base Power Button 5.0% 🛙 OLED Screen Up/Down Button 5

# Mod Operations

1. Power On: While the device is off power, fast click Power Button 5 times in 2s to start up. The screen successively shows "SMOK";

2. Vaping: While the device is power on, hold Power Button to vape (it will be forced to stop working when one vaping is longer than 12s, release once to vape again);

### Fast press the Power Button 5 times to lock or unlock

3. Screen Unlocked Status: 1)Press Power + DOWN Button simultaneously to choose working mode among

TC Mode, VW Mode and MEMORY Mode; 2) Press Power + UP Button simultaneously to choose different effect

Norm/Soft/Hard in WATT MODE or 15-85W in TEMP MODE. 3)Press UP / DOWN Button to adjust the temperature or wattage settings; 4)Press UP and DOWN Button simultaneously to lock/unlock the screen.

7

11

4. Screen Locked Status: Hold the Power Button for 5s and choose POWER OFF to power off.

# 5 Power Off


While the device is locked, hold Power Button for 5s, choose POWER OFF, and the screen turns off, which means the device is power off.

6. Saving: All the settings will be automatically saved while settings done. No need to reset after power on

### 7. Menus & Prompts:

After startup, fast press the POWER Button 3 times in 2s, then you will go to the operation menu. At the same time, long-press on the POWER Button has confirmed function; UP/DOWN Button could do menu moves.

lcon	Name	Briefintroduction
-∿	MODE Switch	TEMP MODE/WATT MODE /MEMORY MODE
	TEMP MODE	1.Choose different effect by pressing Power Button: 15-85W 2.COIL TYPE: TC-NI, TC-TI, TC-SS 3.Adjust Temperature coefficient of resistance
	WATT MODE	Choose different effect by pressing Power Button: STRENGTH HARD, STRENGTH NORM, STRENGTH SOFT
	MEMORY MODE	1.Choose different effect by pressing Power Button: STRENGTH HARD, STRENGTH NORM, STRENGTH SOFT 2.Set M1-M8 by Up/Down Button to increase/decrease the wattage value
~	Vape Data	ALERADY: Puff numbers you have taken; MAX PUFFS: Set limited puff numbers; NEVER: Represents unlimited puffs; PUFFS RESET: puff counter clearing function
Ö	Setting	Press Power Button to enter sub-menu
To	SCR TIME	STEALTH ON: in this mode the display is off. Choose STEALTH OFF, and then set screen saver time (15 seconds to 240 seconds).



	TC Mode Working Temperature Working Voltage TEMP Mode TEMP Mode Coil Type Battery power Wolt I OHNSI AMPE Working Current Sa39 0436 1224 TEMP CON 055 035
	TC Mode is available when AL85 works with a TC type atomizer. 1.Enter TC Mode: switch among TC Mode, VW Mode and MEMORY Mode by
	pressing POWER+ DOWN Button simultaneously while screen is unlocked. 2.Use POWER+ UP Button simultaneously to switch from 15W to 85W. 3.In the TC Mode, please use the UP / DOWN Button to adjust the temperature
	settings with an increment/decrement of 10 Fahrenheit degrees (about 5 Celsius

degrees) to get the best preferred settings. 4.Enter into Coil Material Selection menu. There are three options of

AL85 VW Mode is available for all types of atomizers. 1. Enter VW Mode: switch among TC Mode, VW Mode and MEMORY Mode by

pressing Power Button + DOWN Button simultaneously while screen is unlocked. 2. Use POWER+ UP Button simultaneously to switch among STRENGTH

Temperature Sensing Coil Material for you to choose: TC-NI/TC-TI/TC-SS. 5.Enter into Adjustable Initial Resistance. You can adjust the initial resistance of your atomizer by pressing the Up/Down button. 6.When the screen shows "TEMPERATURE PROTECTED", the heating coil

reached the maximum allowed temperature during the Vaping. If it happens, the AL85 will continue to fire, but will not be able to provide the desired wattage.

### VW Mode.

**Tank Operations** 


it counterclockwise.

airflow tube.

How to fill with e-liquid:



2) Add e-liquid through the slot, and pay attention not to drip in into the central





### **Replace atomizer core:**

14

16

18

15

17

Attentions

Firstly, screw the drip tip and top cap off the tank; then screw the atomizer core off the base part, and replace with a new one.









products or its use, please contact your local SMOK agent or to visit our website www.smoktech.com

3.Please avoid making the e-liquid into your mouth directly. 4.Please do not keep the liquid inside the atomizer if the device is not going to be used for a long period.

1.Before use please read the manual carefully.

5.Please refill the tank when the e-liquid is nearly used out to avoid dry-burning of the atomizer.

2.Connect the atomizer to a power source that is suitable for its intended use.

6.Please do not drop, throw or mishandle this product as the outer shell or inner components may become damaged.

7.In order to prolong the operation of your product, please keep it away from excessive temperature and humid environment. 8.Please keep this product away from children and pregnant women.

# LEGAL DISCLAIMER

Underage sale is prohibited. Depending on your country/region legal smoking age. 18+ and over 21+ in other countries/regions.

### WARNING


This product is not intended for use by persons under legal smoking age, nonsmokers, women who are pregnant or breastfeeding, or persons with or at risk of heart disease, high blood pressure, diabetes, or taking medicine for depression or asthma.

Key	Function(Screen Unlock Status)	Function(Screen Locked Status)	
Power	Fast click 5 times in 2s - Power On; Fast click 5 times - Screen Locked; Fast click 3 times in 2s - Menu Choose; Hold on – Vape; Release - Standby	Long press 5s – choose Power Off to turn off Fast click 5 times - Unlock Screer	
UP	Click Down - Increase the temperature (TC Mode) Click Down - Increase the wattage (VW Mode)		
DOWN	Click Down - reduce the temperature (TC Mode) Click Down - reduce the wattage (VW Mode)		
Power + UP	Click Down - Change TC Effect (15-85W) or VW Effect (Hard/Norm/Soft)		
Power + DOWN	Click Down - Change Working Mode (TC / VW / MEMORY)		

Prompts	Details	
"SMOK"	Power on success	
"SMOK"	Power off success	
BATTERY LOW	Battery power isn't enough, change a battery	
High Input	Battery voltage is higher than need, change a battery	
NO COIL	Atomizer hasn't been detected, attach an atomizer	
NEW COIL?	Atomizer has been detected under TC Mode	
OHMS TOO LOW	Low resistance value has been detected, replace atomizer	

он	MS TOO HIGH	High resistance value has been detected, replace atomizer
لسبا	COIL SHORT	Short circuit has been detected, replace atomizer
TEN		Temperature protection under TC Mode
	DRY COIL NO LIQUIDDRY COIL NO LIQUID	Atomizer coil is heating without liquid under TC Mode, fill juice





项目名称	Al85 Kit	图纸编号	80110380011
DRAWING	说明书	DRAWING NO.	
设计师 DESIGNED BY	王碧林	审核 APPROVED	
尺寸 SCALE	90*57 mm	工艺 CRAFT	封面字体烫银
材质	封面黑色皮纹(加厚纸张)	日期	2017.01.10
MATERIAL QUALITY	内页128g 铜版纸	DATE	